



MODEL

56K

STAINLESS STEEL CENTRIFUGE PACKAGE

Specification Sheet



Centrifuge type:	56K
Material of construction:	Stainless Steel
Bowl diameter:	14"
Bowl length:	56"
Conveyor type:	E-Z FLOW DESIGN WITH AXIAL FLOW BLADES
Conveyor wear protection:	Tungsten carbide segments
Conveyor lead and pitch:	Single 4.25"
Gear unit type:	3.5 (planetary)
Gear unit ratio:	57-1RATIO
Torque out style:	GS COUPLING
Bowl sheave diameter:	5G3V5.750
Pool depth setting:	4 Adjustable 360 degree dams
Main drive motor:	50 HP
Oilfield skid:	118" X 76" X 43"
Controls:	50VFD main/ 20VFD back drive
Back Drive Motor:	20 HP
Maximum speed:	4000 RPM
Maximum G-Force:	3180
Maximum flow:	150- 200 GPM @ 9.8 P. P. G.

GreySun Equipment Company

3102 Ave M Extended Conroe, Texas 77301 (936) 524-5162 centrifugeco.com



MODEL

56K



GREYSUN
EQUIPMENT COMPANY

STAINLESS STEEL CENTRIFUGE PACKAGE



GreySun Equipment Company

3102 Ave M Extended Conroe, Texas 77301 (936) 524-5162 centrifugeco.com